

Automatic Leaf Wetness Recorder



“Virtual” make Automatic Leaf Wetness Recorder is a fully computerized, digital and self contained power source system, fitted with IP65 Data Logger and battery charging solar panel with rechargeable, maintenance free batteries complete with sensors mounted on a tripod stand with sealed waterproof enclosure for Data Logger, Solar charger and battery.

Features:

- Display: 16 Characters X 2 Lines alphanumeric display,
- Keyboard: 4x2 membrane keypad for onsite programming of data logger.
- Measured Parameter – **Date, Time, Leaf Wetness, Air Temperature, RH & Battery Voltage.**
- Real Time Clock accuracy: Internal with ± 2 minutes / year & leap year compensation
- Number of Channels: 8 can be extendable up to 16 channels (at extra cost)
- Channels Configuration: Factory configured sensors as per purchase order.
- Logging Interval: 1 min to 24 Hr program log Start time within next 24 hours
- Data Storage: store 1 year data at user’s selectable 1 hour logging interval.
- Operating Temperature: - 40 to 75 °C. Humidity: 0 to 95 % non-condensing.
- Power Supply: 12V SMF battery, Charging: Solar Panel / 220V AC (Optional).
- Solar Panel:: 12 Volt DC, Wattage: 10, 20 & 40 Watt (as per system power requirement)
- Battery Life: More than 1.5 Years (Easily Available in local Market)
- Along with Small Stainless Steel Tripod
- Data retrieval: Data shuttle (default). Other options also available (at extra cost).

Other options: Ethernet, 2G/3G/4G enabled Web based telemetry at Virtual’s Portal “www.ehydromet.in”.

Air Temperature & Relative Humidity Sensor:



Temperature Range: - 40 to 123.8 ° C.
 Accuracy: ± 0.5 ° C @ 5 to 40° C.
 Resolution: 0.01 ° C Typical.
 RH Range: 0 to 100 %.
 Resolution: 0.5 % RH Typical.
 Accuracy: $\pm 2\%$ @ 20 to 80 %
 Long term stability: Typ <1%RH/ Year
 Repeatability: ± 0.1 %.

Leaf Wetness Sensor:



Sensor Output: Resistance varies from above 3,000,000 ohms when dry to around 1, 000 ohms when wet
 Sensor Range: 0 to 100% of the dew range, frost and freezing conditions will not harm the sensor
 Response Time: 0 to 100% relative dew within six minutes
 Output: voltage output (Analog)

Application Software (Virtualware)

This is a user-friendly, Menu Driven, Windows based software allows you to view & save collected data from data logger to computer / laptop. Data file is saved in Microsoft’s Excel Format

Ordering Guide:

SN	Description	Model No.
1	LWR with Data Shuttle option	LWR -VH-SS-D
2	LWR with Ethernet option	LWR -VH-SS-E
3	LWR with 2G/3G/4G WEB-based Telemetry	LWR -VH-SS-GPRS

Virtual

Hydromet

1105/1, Salempur Rajputana Industrial Estate
 Roorkee- 247667, Haridwar, Uttarakhand, INDIA
 Tel:+91-7088-772-772, vhydromet@yahoo.com



Represented by:

****Drawing / specifications are subjected to change at any time without prior notice as per manufacturing suitability.**